
django-simple-friends Documentation

Release 1.1.0

Atamert Ölçgen

Mar 05, 2017

Contents

1	About django-simple-friends	3
1.1	Highlights	3
2	Setting up django-simple-friends	5
2.1	Installation	5
2.2	Development Setup	5
3	Changes	7
3.1	Version 1.0.0 - Mar 16, 2013	7
3.2	Version 0.5 - Oct 7, 2012	7
3.3	Version 0.4 - Feb 4, 2010	7
4	Package Reference	9
4.1	How to display a list of friends for a user	9
5	Package Reference	11
5.1	Views	11
5.2	Models	12
5.3	Signals	14
5.4	Signal Handlers	14
6	Indices and tables	15
	Python Module Index	17

Contents:

CHAPTER 1

About django-simple-friends

I started developing *django-simple-friends* when I needed a simple app that handles friendships for my project. *django-friends* of *Pinax* was mature and well written but it was also handling contacts and invitations. So I decided to create my own app and steal some ideas from *django-friends*.

You can get community support at the [mailing list](#).

Highlights

- Only the relationships between registered users are managed.
- Friending with double confirmation. When a user adds another user as a friend, only when the other user accepts or tries to add the first user as a friend, the friendship relationship is created.
- Blocking is possible.

Setting up django-simple-friends

Installation

1. Install *django-simple-friends* package:

```
pip install django-simple-friends
```

2. Add *friends* to your *INSTALLED_APPS* setting:

```
INSTALLED_APPS = (  
    # Other apps  
    'friends',  
)
```

3. Run *syncdb* to create tables and seed friendship data for existing users:

```
python manage.py syncdb
```

4. Run tests to make sure the app is installed correctly:

```
python manage.py test friends
```

5. Optionally include *friends.urls* to your URLconf:

```
urlpatterns = patterns('',  
    # Other entries  
    (r'^friends/', include('friends.urls')),  
)
```

Development Setup

If you want to develop *django-simple-friends* you can follow the steps below to set up a development environment.

1. Log-in to your GitHub account and [fork the project](#).
2. Create a virtual environment:

```
virtualenv --no-site-packages django-simple-friends
```

3. Create a local repository:

```
cd django-simple-friends  
. bin/activate  
git clone git@github.com:muhuk/django-simple-friends.git src
```

Warning: You need to replace *muhuk* with your GitHub username in the command above.

4. Run the tests to make sure everything is set up correctly:

```
cd src  
python example/manage.py test friends
```

5. Pick an [issue](#) to work on.

CHAPTER 3

Changes

Version 1.0.0 - Mar 16, 2013

- Some view classes are renamed:

BaseFriendshipActionView	->	BaseActionView
FriendshipBlockView	->	UserBlockView
FriendshipUnblockView	->	UserUnblockView

If you are using only the view functions or the provided `urls.py`, then you don't need to change your code.

- `related_name`'s for the `ForeignKey`'s to `User` from `FriendshipRequest` are changed as `friendshiprequests_from` and `friendshiprequests_to`. Please replace any references to `invitations_from` and `invitations_to` in your code.

Version 0.5 - Oct 7, 2012

Tested with Django versions **1.3** & **1.4**.

- `friend_list` view is removed. See `friends` template filter.
- View functions are rewritten as class based views. But they still work as aliases.
- `post_syncdb` signals to fix the issue of Users without Friendships.
- Proper Sphinx powered documentation.
- German & Spanish translations.

Version 0.4 - Feb 4, 2010

- Initial release.

How to display a list of friends for a user

Use `friends()` template filter to obtain a `QuerySet` containing the `User`'s who are friends with the filter's argument:

```
{% load friends %}
<h3>Friends</h3>
<ul>{% for friend in user|friends %}
    <li>{{ friend.get_full_name }}</li>
{% endfor %}</ul>
```

The code above should produce a result like this:

```
<h3>Friends</h3>
<ul>
    <li>Lenda Murray</li>
    <li>Sharon Bruneau</li>
    <li>Cory Everson</li>
</ul>
```


Views

Class Based Views

All the views are implemented as `classes` but *view functions* are also provided.

```
class friends.views.BaseActionView(**kwargs)
```

Base class for action views.

```
    set_url(request, **kwargs)
```

Set the `url` attribute so that it can be used when `get_redirect_url()` is called.

`url` is determined using the following methods, in order:

- It can be set in the `urlconf` using `redirect_to` keyword argument.
- If `redirect_to_param` keyword argument is set in `urlconf`, the request parameter with that name will be used. In this case the request parameter **must** be provided in runtime.
- If the request has `redirect_to` to parameter is present, its value will be used.
- If `REDIRECT_FALLBACK_TO_PROFILE` setting is `True`, current user's profile URL will be used.
- `HTTP_REFERER` header's value will be used if exists.
- If all else fail, `' / '` will be used.

```
class friends.views.FriendshipAcceptView(**kwargs)
```

```
class friends.views.UserBlockView(**kwargs)
```

```
class friends.views.FriendshipCancelView(**kwargs)
```

```
class friends.views.FriendshipDeclineView(**kwargs)
```

```
class friends.views.FriendshipDeleteView(**kwargs)
```

```
class friends.views.FriendshipRequestView(**kwargs)
```

```
class friends.views.UserUnblockView (**kwargs)
```

View Functions

Tip: If you want to customize the views provided, check out *Class Based Views* first.

```
friends.views.friendship_request (request, *args, **kwargs)
friends.views.friendship_accept (request, *args, **kwargs)
friends.views.friendship_decline (request, *args, **kwargs)
friends.views.friendship_cancel (request, *args, **kwargs)
friends.views.friendship_delete (request, *args, **kwargs)
friends.views.user_block (request, *args, **kwargs)
friends.views.user_unblock (request, *args, **kwargs)
```

Models

```
class friends.models.FriendshipRequest (*args, **kwargs)
```

An intent to create a friendship between two users.

See also:

There should never be complementary *FriendshipRequest*'s, as in user1 requests to be friends with user2 when user2 has been requested to be friends with user1. See how *FriendshipRequestView* checks the existence of a *FriendshipRequest* from to_user to from_user.

accept ()

Create the *Friendship* between from_user and to_user and mark this instance as accepted.

friendship_accepted is signalled on success.

See also:

FriendshipAcceptView

cancel ()

Deletes this *FriendshipRequest*

friendship_cancelled is signalled on success.

See also:

FriendshipCancelView

decline ()

Deletes this *FriendshipRequest*

friendship_declined is signalled on success.

See also:

FriendshipDeclineView

```
class friends.models.FriendshipManager
```


are_friends (*user1*, *user2*)

Indicate if *user1* and *user2* are friends.

Parameters

- **user1** (*User*) – User to compare with *user2*.
- **user2** (*User*) – User to compare with *user1*.

Return type `bool`

befriend (*user1*, *user2*)

Establish friendship between *user1* and *user2*.

Important: Instead of calling this method directly, *FriendshipRequest.accept()*, which calls this method, should be used.

Parameters

- **user1** (*User*) – User to make friends with *user2*.
- **user2** (*User*) – User to make friends with *user1*.

friends_of (*user*, *shuffle=False*)

List friends of *user*.

Parameters

- **user** (*User*) – User to query friends.
- **shuffle** (*bool*) – Optional. Default `False`.

Returns `QuerySet` containing friends of *user*.

unfriend (*user1*, *user2*)

Break friendship between *user1* and *user2*.

Parameters

- **user1** (*User*) – User to unfriend with *user2*.
- **user2** (*User*) – User to unfriend with *user1*.

class `friends.models.Friendship` (**args*, ***kwargs*)

Represents the network of friendships.

friend_count ()

Return the count of friends. This method is used in `FriendshipAdmin`.

Return type `int`

friend_summary (*count=7*)

Return a string representation of friends. This method is used in `FriendshipAdmin`.

Parameters **count** (*int*) – Maximum number of friends to include in the output.

Return type `unicode`

class `friends.models.UserBlocks` (**args*, ***kwargs*)

User’s blocked by *user*.

block_count ()

Return the count of blocks. This method is used in `UserBlocksAdmin`.

Return type `int`

block_summary (*count=7*)

Return a string representation of `blocks`. This method is used in `UserBlocksAdmin`.

Parameters `count` (*int*) – Maximum number of blocked users to include in the output.

Return type `unicode`

Signals

friendship_accepted

`friends.signals.friendship_accepted`

Sent when a *FriendshipRequest* is accepted.

Arguments sent with this signal:

sender *FriendshipRequest* instance that is accepted.

friendship_declined

`friends.signals.friendship_declined`

Sent when a *FriendshipRequest* is declined by `to_user`.

Arguments sent with this signal:

sender *FriendshipRequest* instance that is declined.

friendship_cancelled

`friends.signals.friendship_cancelled`

Sent when a *FriendshipRequest* is cancelled by `from_user`.

Arguments sent with this signal:

sender *FriendshipRequest* instance that is cancelled.

Signal Handlers

`signals.create_friendship_instance` (*sender, instance, created, raw, **kwargs*)

Create a *FriendshipRequest* for newly created *User*.

See also:

`post_save` built-in signal.

`signals.create_userblocks_instance` (*sender, instance, created, raw, **kwargs*)

Create a *UserBlocks* for newly created *User*.

See also:

`post_save` built-in signal.

CHAPTER 6

Indices and tables

- `genindex`
- `modindex`
- `search`

f

`friends.models`, [12](#)
`friends.signals`, [14](#)
`friends.views`, [11](#)

A

`accept()` (`friends.models.FriendshipRequest` method), 12
`are_friends()` (`friends.models.FriendshipManager` method), 12

B

`BaseActionView` (class in `friends.views`), 11
`befriend()` (`friends.models.FriendshipManager` method), 13
`block_count()` (`friends.models.UserBlocks` method), 13
`block_summary()` (`friends.models.UserBlocks` method), 14

C

`cancel()` (`friends.models.FriendshipRequest` method), 12
`create_friendship_instance()` (`friends.signals` method), 14
`create_userblocks_instance()` (`friends.signals` method), 14

D

`decline()` (`friends.models.FriendshipRequest` method), 12

F

`friend_count()` (`friends.models.Friendship` method), 13
`friend_summary()` (`friends.models.Friendship` method), 13
`friends.models` (module), 12
`friends.signals` (module), 14
`friends.signals.friendship_accepted` (in module `friends.signals`), 14
`friends.signals.friendship_cancelled` (in module `friends.signals`), 14
`friends.signals.friendship_declined` (in module `friends.signals`), 14
`friends.views` (module), 11
`friends_of()` (`friends.models.FriendshipManager` method), 13
`Friendship` (class in `friends.models`), 13
`friendship_accept()` (in module `friends.views`), 12
`friendship_cancel()` (in module `friends.views`), 12

`friendship_decline()` (in module `friends.views`), 12
`friendship_delete()` (in module `friends.views`), 12
`friendship_request()` (in module `friends.views`), 12
`FriendshipAcceptView` (class in `friends.views`), 11
`FriendshipCancelView` (class in `friends.views`), 11
`FriendshipDeclineView` (class in `friends.views`), 11
`FriendshipDeleteView` (class in `friends.views`), 11
`FriendshipManager` (class in `friends.models`), 12
`FriendshipRequest` (class in `friends.models`), 12
`FriendshipRequestView` (class in `friends.views`), 11

S

`set_url()` (`friends.views.BaseActionView` method), 11

U

`unfriend()` (`friends.models.FriendshipManager` method), 13
`user_block()` (in module `friends.views`), 12
`user_unblock()` (in module `friends.views`), 12
`UserBlocks` (class in `friends.models`), 13
`UserBlockView` (class in `friends.views`), 11
`UserUnblockView` (class in `friends.views`), 11